

Sub F4

Eq

47. (Amended) An article comprising;
- a) a substrate; and
 - b) a flexible clear polyurethane applied as a layer on a surface of said substrate, said flexible polyurethane comprising a reaction product of,
 - i) a first component included one or more polyols having an equivalent weight in the range from about 28 to about 3000, optionally one or more diols having an equivalent weight in the range from about 30 to about 4000, and a catalyst; and
 - ii) a second component comprising a primary aliphatic isocyanate crosslinker having at least 50 weight percent polyisocyanate,
- wherein the first and second components together are solvent free.

53. (New) An article as recited in claim 41, wherein the first component comprises greater than about 20 weight percent polyester.

54. (New) An article as recited in claim 26, wherein said clear polyurethane protective layer has a curved outer surface.

55. (New) An article as recited in claim 41, wherein said clear protective polyurethane layer has a curved outer surface.

56. (New) An article as recited in claim 45, wherein said clear polyurethane protective layer has a curved outer surface.

57. (New) An article as recited in claim 47, wherein said clear polyurethane layer has a curved outer surface.

Remarks

Claims 41 and 47 are amended. New claims 53-57 are added. These changes are supported by the specification and add no new matter to the application.

A marked up version of the claims is provided to show the changes made.

Claims 26-36 and 38-57 are pending.